

A10 Thunder on Dell Technologies OEM Solution Bundle

Single Service Platform (SSP) Specifications

The SSP range consists of A10's cloud-ready software and purpose-built Dell Technologies hardware, with an inclusive license*4 that has the capabilities of delivering Application Delivery Controller (ADC), SSL Insight (SSLi), and CGN (Carrier Grade Networking) solutions along with an expanded feature set of A10 capabilities.

	Dell Technologies VEP4600	Dell Technologies R640		Dell Technologies R740	
		10GE NIC Model	100GE NIC Model	10GE NIC Model	100GE NIC Model
Thunder ADC Performance					
Application Throughput (L4 / L7)	10 Gbps / 7.5 Gbps	40 Gbps / 40 Gbps	60 Gbps / 60 Gbps	75 Gbps / 75 Gbps	100 Gbps / 100 Gbps
Connections Per Second (L4 / L7)*1	350K / 175K	2 Million / 1 Million	2 Million / 1 Million	2 Million / 1 Million	3 Million / 1 Million
SSL Bulk Throughput	2 Gbps	32 Gbps	38 Gbps	45 Gbps	66 Gbps
SSL CPS (RSA / ECDSA)*2	3.5K / 7K	100K / 45K	107K / 72K	120K / 60K	131K / 85K
Thunder CGN Performance					
Throughput	12 Gbps	30 Gbps	60 Gbps	60 Gbps	100 Gbps
Full TCP Connections Per Second	500K	1.5 Million	1.5 Million	2 Million	2 Million
Concurrent Sessions	50 Million	100 Million	100 Million	100 Million	100 Million
Thunder SSLi Performance*3					
SSL Insight Throughput	Not Supported	8.5 Gbps	12.5 Gbps	16.5 Gbps	30 Gbps
SSL Insight CPS (RSA / ECDHE)	Not Supported	28.5K / 13.5K	28.5K / 14.5K	30K / 18.5K	30K / 18.5K
SSL Insight Concurrent Sessions	Not Supported	3 Million	3 Million	3 Million	3 Million
Network Interface					
1 GE (BASE-T)	6	2	2	2	2
1/10 GE Fiber (SFP+)	4	6	2	10	10
100 GE Fiber (QSFP28)	0	0	2	0	4
Hardware Specifications					
Processor	1 x Intel Xeon 8-core	2 x Intel Xeon 20-core		2 x Intel Xeon 20-core	
Memory	16 GB	192 GB		192 GB	
Storage	SSD	2 x SSD		2 x SSD	
TLS/SSL Security Processor	Built-in	2 x Security card (PCIe)		2 x Dual-chip security card (PCIe)	
Power Supply	Single 230W Power Supply	Dual 750W Power Supply		Dual 2000W Power Supply	

*1 Layer 7 connections per second - measures number of new HTTP connections (1 HTTP request per TCP connection, without TCP connection reuse) within 1 second

*2 RSA (2K keys) cipher: "TLS_RSA_WITH_AES_128_CBC_SHA", ECDSA (EC P-256) cipher: "TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA"

*3 SSLi performance is tested in L3, dual-partition mode deployment, with RSA (2K keys) cipher "TLS_RSA_WITH_AES_128_CBC_SHA" and ECDSA (EC P-256) cipher "TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA"

*4 A10 Thunder on Dell Technologies OEM bundle solutions are licensed under the Convergent Firewall (CFW) license. Check with your A10 Networks sales representative for the latest information on full feature testing and validation.

Multi-tenant Virtual Platform (MVP) Specifications

A10 Thunder Multi-tenant Virtual Platform (MVP) on Dell Technologies is an advanced platform enabling multiple virtual instances or services on a single platform, with an inclusive license*4 that has the capabilities of delivering Application Delivery Controller (ADC), SSL Insight (SSLi), and CGN (Carrier Grade Networking) solutions along with an expanded feature set of A10 capabilities.

	Dell Technologies R640		Dell Technologies R740	
Performance with ADC	10GE NIC Model	100GE NIC Model	10GE NIC Model	100GE NIC Model
Application Throughput (L4 / L7)	40 Gbps / 40 Gbps	43 Gbps / 36 Gbps	75 Gbps / 75 Gbps	93 Gbps / 72 Gbps
Connections Per Second (L4 / L7)**	950K / 700K	1 Million / 850K	1.2 Million / 1 Million	1.7 Million / 1.7 Million
SSL Bulk Throughput	32 Gbps	37 Gbps	40 Gbps	63 Gbps
SSL CPS (RSA / ECDSA)*2	60K / 45K	98.6K / 75K	120K / 90K	164K / 116K
Performance with CGNAT				
Throughput	32 Gbps	60 Gbps	56 Gbps	120 Gbps
Full TCP Connections Per Second	750K	850K	1.5 Million	1.5 Million
Concurrent Sessions	100 Million	220 Million	140 Million	220 Million
Performance with SSL Insight*3				
SSL Insight Throughput	6.8 Gbps	15.5 Gbps	13.8 Gbps	32.5 Gbps
SSL Insight CPS (RSA / ECDHE)	12.5K / 7K	55K / 32K	27K / 14K	68.5K / 52.5K
SSL Insight Concurrent Sessions	58K	680K	118K	680K
Network Interface				
1 GE (BASE-T)	2	2	2	2
1/10 GE Fiber (SFP+)	6	2	10	10
100 GE Fiber (QSFP28)	0	2	0	4
Hardware Specifications				
Processor	2 x Intel Xeon 20-core		2 x Intel Xeon 20-core	
Memory	192 GB		192 GB	
Storage	2 x SSD		2 x SSD	
TLS/SSL Security Processor	2 x Security card (PCIe)		2 x Dual-chip security card (PCIe)	
Power Supply	Dual 750W Power Supply		Dual 2000W Power Supply	

*1 Layer 7 connections per second - measures number of new HTTP connections (1 HTTP request per TCP connection, without TCP connection reuse) within 1 second

*2 RSA (2K keys) cipher: "TLS_RSA_WITH_AES_128_CBC_SHA", ECDSA (EC P-256) cipher: "TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA"

*3 SSLi performance is tested in L3, dual-partition mode deployment, with RSA (2K keys) cipher "TLS_RSA_WITH_AES_128_CBC_SHA" and ECDSA (EC P-256) cipher "TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA"

*4 A10 Thunder on Dell Technologies OEM bundle solutions are licensed under the Convergent Firewall (CFW) license. Check with your A10 Networks sales representative for the latest information on full feature testing and validation.

All Thunder MVP performance specifications are aggregate numbers that use the following VM profiles:

For ADC and CGNAT:

- R640 10GE NIC model is tested with 4-VM profile (8 vCPUs, 16 GB memory, 30 GB storage, 16 SSL virtual functions (VFs) assigned on each vThunder)
- R640 100GE NIC model is tested with 4-VM profile (16 vCPUs, 32 GB memory, 30 GB storage, 8 SSL VFs assigned on each vThunder)
- R740 10GE and 100GE NIC models are tested with 8-VM profile (8 vCPUs, 16 GB memory, 30 GB storage, 16 SSL VFs assigned on each vThunder)

For SSL Insight:

- R640 10GE NIC model is tested with 1 VM and R740 10GE NIC model is with 2 VMs. Each vThunder is assigned with 8 CPUs, 16 GB memory, 30 GB storage, 8 SSL VFs.
- Both R640 and R740 100GE NIC models are tested with 4-VM profile (16 vCPUs, 32 GB memory, 30 GB storage, 16 SSL VFs assigned on each vThunder)

Learn More

About A10 and Dell Technology

Contact Us

dellteam@a10networks.com
a10networks.com/contact

©2021 A10 Networks, Inc. All rights reserved. A10 Networks, the A10 Networks logo, ACOS, A10 Thunder, Thunder TPS, A10 Lightning, A10 Harmony, and SSL Insight are trademarks or registered trademarks of A10 Networks, Inc. in the United States and other countries. All other trademarks are property of their respective owners. A10 Networks assumes no responsibility for any inaccuracies in this document. A10 Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice. For the full list of trademarks, visit: www.a10networks.com/a10-trademarks.

Part Number: A10-DS-15131-EN-03 FEB 2021